

# NK80 A (130 gsm) Technical Data Sheet

## 80 lb Anti Slip Paper

### Grade: NK80 A

| Parameter               | Value                         |
|-------------------------|-------------------------------|
| Basis Weight (lbs/ream) | 80.0 (3000 sq. ft.) (24"x36") |
| Caliper (mils)          | 7.5                           |
| Slipping Angle (FS)     | 55 Degrees                    |
| Slipping Angle (BS)     | 55 Degrees                    |
| Bending Stiffness (MD)  | 14                            |
| Bending Stiffness (CD)  | 22                            |
| Cobb (FS)               | 14                            |
| Cobb (BS)               | 14                            |
| Moisture                | 7.0 %                         |

Natural shade appearance and manufactured from 100% Natural Kraft. Coated paper imparts anti slip performance. Visit our website to learn more about the NK80 A Anti Slip Paper at <http://www.appliedconverting.com/anti-slip-paper/80-lb-anti-slip-paper-nk80-a/>

- Excellent sheet for interleaving slippery products.
- Locks layers of material together to create a solid load.
- Non-adhesive and made with 100% natural Kraft fiber.
- Idea for interleaving boxes, bags, cartons, cases and plastic.
- Reduce stretch wrap cost, also available in 65, 90 and 138 lb. weights.



Applied  
Coating and  
Converting, LLC.

*"Specialty Coated Papers"*

3736 Wells Street  
Fort Wayne, Indiana 46808